

CP- UVR-0401E1S-V3**4 Ch. 720P HDCVI DVR****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-0401E1S-V3

4 Ch. 720P HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Max User Account
 Interface Ports
 Record Interval
 Ethernet
 Protocols
 Power Supply
 Power Consumption

Specification

Embedded processor
 Embedded LINUX
 Reuse audio input/output channel 1
 GUI
 4 channel,BNC
 1 HDMI, 1 VGA
 Analog: NTSC/ PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 4+1 up to 5MP
 H.264 / G.711
 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
 Main Stream:1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF(1~25/30fps), Extra Stream: CIF/QCIF (1~15fps)
 1/4/6
 4 rectangular zones (each camera)
 1 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 iPhone, iPad, Android, Windows Phone
 1 SATA port, up to 6TB
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file,
 USB Device/Internal SATA burner/Network
 128 users
 1 HDMI, 1 VGA, 2 USB2.0, 1 RS485
 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 RJ-45 port (10/100M)
 HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P
 DC12V/1.5A
 10W(without HDD)



 **CP- UVR-0401E1S-V3****4 Ch. 720P HDCVI DVR****Feature**

Working Temp

Dimensions

Weight

Specification

-10 ~+55°C / 10~90%RH / 86~106kpa

Smart 1U, 205 mm×205 mm×40 mm

0.5KG(without HDD)