

CP- UVR-0401K1-V3**4 Ch. 720P HDCVI DVR****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P realtime or 1080P non-realtime recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-0401K1-V3

4 Ch. 720P HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Hard Disk
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode

Specification

Embedded processor
 Embedded LINUX
 Reuse audio input/output channel 1
 GUI
 4 channel, BNC
 1 HDMI, 1 VGA
 Analog: NTSC/PAL, HDCVI: 1080P/720P HDCVI Camera , IP: 4+2 up to 5Mp
 H.264 / G.711
 1920×1080, 1280×1024, 1280×720, 1024×768
 Main Stream:1080P(1~15fps) 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) Extra Stream:D1/CIF/QCIF(1~15fps)
 1/4/6
 4 rectangular zones (each camera)
 1 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 1 SATA port, up to 6TB
 iPhone, iPad, Android, Windows Phone
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)

Playback
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

Backup Mode
 USB Device/Internal SATA burner/Network
 128 users
 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 1 HDMI, 1 VGA, 2 USB2.0
 RJ-45 port (10/100M)
 HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P





CP- UVR-0401K1-V3

4 Ch. 720P HDCVI DVR



Feature

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

DC12V/2A

10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

205mm × 205mm × 40mm

0.5KG(without HDD)



*Product casing and specifications are subject to change without prior notice