

**CP- UVR-0404K1-V3****4 Ch. 720P HDCVI DVR****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P realtime or 1080P non-realtime recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



# CP- UVR-0404K1-V3

## 4 Ch. 720P HDCVI DVR



### Feature

Processor  
Operating System  
Two-way Talk  
User Interface  
Video Input  
Video Output  
Video Standard  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Privacy Masking  
Audio Input  
Audio Output  
Motion Detection  
Video Loss  
Camera Blank  
Alarm Input  
Alarm Output  
Smart Phone  
Hard Disk  
Trigger Events  
Recording Mode  
Search Mode  
  
Playback  
  
Backup Mode  
Interface Ports  
Record Interval  
Max User Account

### Specification

Embedded processor  
Embedded LINUX  
Reuse audio input/output channel 1  
GUI  
4 channel, BNC  
1 HDMI, 1 VGA  
Analog: NTSC/ PAL, HDCVI: 1080P/720P ,IP:4+2 up to 5Mp  
H.264 / G.711  
1920×1080, 1280×1024, 1280×720, 1024×768  
Main Stream:1080P(1~15fps) 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) Extra Stream:D1/CIF/QCIF(1~15fps)  
1/4/6  
4 rectangular zones (each camera)  
4 channel, RCA  
1 channel, RCA  
Supports  
Supports  
Supports  
4 channel  
3 Channel  
iPhone, iPad, Android, Windows Phone  
1 SATA port, up to 6TB  
Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips  
Manual, Schedule(Regular(Continuous), MD), Stop  
Time/Date, MD & Exact search (accurate to second)  
  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom  
  
USB Device/Internal SATA burner/Network  
1 HDMI, 1 VGA, 2 USB2.0  
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
128 users



# CP- UVR-0404K1-V3

4 Ch. 720P HDCVI DVR



## Feature

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

## Specification

RJ-45 port (10/100M)

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P

DC12V/2A

10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

325mm × 255mm × 55mm

1.5KG(without HDD)