

CP- UVR-0808K8D**8 Ch. 720P-Advanced Tribrid HDCVI DVR****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 720P Realtime or 1080P non-Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support Multi-brand network cameras
- Support 8 SATA HDD up to 32TB, 1 eSATA, 4 USB2.0, DVDRW
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UVR-0808K8D

8 Ch. 720P-Advanced Tribrid HDCVI DVR



Feature

Processor
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Privacy Masking
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Hard Disk
Smart Phone
Trigger Events
Recording Mode
Search Mode

Playback

Backup Mode
Max User Account
Record Interval
Interface Ports
Ethernet

Specification

Embedded processor
Embedded LINUX
1 channel Input, 1 channel Output, BNC
GUI
8 channel, BNC
1 HDMI, 1 VGA, 1 TV
Analog: NTSC/PAL, HDCVI: 1080P/720P HDCVI Camera, IP: Support 2ch 1080P/720P IP Cam-
H.264 / G.711
1920×1080, 1280×1024, 1280×720, 1024×768
Main Stream: 1080P(1~12/15fps) / 720P/960H / D1(1~25/30fps), Extra Stream: CIF / QCIF
1/4/8/9
4 rectangular zones (each camera)
8 channel, RCA
1 channel, RCA
Supports
Supports
Supports
8 channel
6 channel
8 SATA ports(8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB, 1 eSATA port, up to 16TB
iPhone, iPad, Android, Windows Phone
Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Manual, Schedule(Regular(Continuous), MD), Stop
Time/Date, MD & Exact search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous
camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

USB Device/Internal SATA burner/Network
128 users
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
1 HDMI, 1 VGA, 4 USB2.0, 1 RS485, 1RS232
2RJ-45 port (10/100M/1000M)

CP- UVR-0808K8D**8 Ch. 720P-Advanced Tribrid HDCVI DVR****Feature**

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance

AC 100~240 V, 50/60 Hz

40W(Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm × 460mm × 89mm

6.5KG(without HDD)